TILE RITE RAPID DRY AEROSOL 600ML

Page: 1

Compilation date: 18/05/2014

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TILE RITE RAPID DRY AEROSOL 600ML

Product code: RDS042

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Natural Stone & Tile Impregnator Wall & Floor Grout Protector

1.3. Details of the supplier of the safety data sheet

Company name: TILE RITE

Unit 2 Phoenix Road Hawks Green, Cannock Staffordshire WS11 7LR United Kingdom Tel: +44 (0)1543 500893

.

Email: laura@tilerite.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

| 2.1. Classification of the substance or mixture | | |
|---|---|--|
| Classification under CHIP: | F: R11; Xi: R36; -: R52/53; -: R66; -: R67 | |
| Classification under CLP: | Eye Irrit. 2: H319; Aquatic Chronic 3: H412; Flam. Liq. 1: H224; STOT SE 3: H336 | |
| Most important adverse effects: | Highly flammable. Irritating to eyes. Harmful to aquatic organisms, may cause long-term | |
| | adverse effects in the aquatic environment. Repeated exposure may cause skin dryness | |
| | or cracking. Vapours may cause drowsiness and dizziness. | |

2.2. Label elements

| Label elements under CLP: | | | |
|---------------------------|--|--|--|
| Hazard statements: | H224: Extremely flammable liquid and vapour. | | |
| | H319: Causes serious eye irritation. | | |
| | 1336: May cause drowsiness or dizziness. | | |
| | H412: Harmful to aquatic life with long lasting effects. | | |
| Signal words: | Danger | | |
| Hazard pictograms: | GHS02: Flame | | |
| | GHS07: Exclamation mark | | |
| | \wedge \wedge | | |



Page: 2

| | TILE RITE RAPID DRY AEROSOL 600ML |
|----------------------------|---|
| | |
| Precautionary statements: | P280: Wear protective gloves/protective clothing/eye protection/face protection. |
| | P210: Keep away from open flames No smoking. |
| | P233: Keep container tightly closed. |
| | P242: Use only non-sparking tools. |
| | P240: Ground/Bond container and receiving equipment. |
| | P241: Use explosion-proof ventilating equipment. |
| | P261: Avoid breathing spray. |
| | P271: Use only outdoors or in a well-ventilated area. |
| | P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. |
| | Rinse skin with water. |
| | P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position |
| | comfortable for breathing. |
| | P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove |
| | contact lenses, if present and easy to do. Continue rinsing. |
| | P312: Call a POISON CENTER or doctor if you feel unwell. |
| | P370+378: In case of fire: Use appropriate fire extinguisher for extinction. |
| Label elements under CHIP: | |
| Hazard symbols: | Highly flammable. |

Hazard symbols:Highly flammable.Irritant.Image: Irritant in the symbol in the sym

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

TILE RITE RAPID DRY AEROSOL 600ML

Page: 3

Hazardous ingredients:

ACETONE

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------|---------|---------------------------------|---|---------|
| 200-662-2 | 67-64-1 | F: R11; Xi: R36; -: R66; -: R67 | Flam. Liq. 2: H225; Eye Irrit. 2: H319; | 50-70% |
| | | | STOT SE 3: H336; -: EUH066 | |

PROPANE

| 200-82 | 7-9 | 74-98-6 | F+: R12 Substance with a Community | Flam. Gas 1: H220; Press. Gas: H280 | 10-30% |
|--------|-----|---------|---------------------------------------|-------------------------------------|--------|
| | | | workplace exposure limit. | | |

N-BUTYL ACETATE

| 204-658-1 | 123-86-4 | -: R10; -: R66; -: R67 | Flam. Liq. 3: H226; STOT SE 3: H336; | 1-10% |
|-----------|----------|----------------------------|--------------------------------------|-------|
| | | Substance with a Community | -: EUH066 | |
| | | workplace exposure limit. | | |

KEROSINE - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

| 265-149-8 | 64742-47-8 | Xn: R65; N: R51/53 | Asp. Tox. 1: H304; Aquatic Chronic 2: | 1-10% |
|-----------|------------|--------------------|---------------------------------------|-------|
| | | | H411 | |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water

spray to cool containers.

TILE RITE RAPID DRY AEROSOL 600ML

| | Page: 4 |
|---------------------------------|--|
| 5.2. Special hazards arising f | rom the substance or mixture |
| Exposure hazards: | Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. |
| | Vapour may travel considerable distance to source of ignition and flash back. |
| 5.2 Advice for fire fighters | · · · · · · · · · · · · · · · · · · · |
| 5.3. Advice for fire-fighters | |
| Advice for fire-fighters: | Wear self-contained breathing apparatus. Wear protective clothing to prevent contact |
| | with skin and eyes. |
| Section 6: Accidental release | e measures |
| | |
| 6.1. Personal precautions, pr | otective equipment and emergency procedures |
| Personal precautions: | Refer to section 8 of SDS for personal protection details. If outside do not approach from |
| | downwind. If outside keep bystanders upwind and away from danger point. Mark out the |
| | contaminated area with signs and prevent access to unauthorised personnel. Turn |
| | leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of |
| | ignition. |
| 6.2. Environmental precautio | ns |
| | |
| Environmental precautions: | Do not discharge into drains or rivers. Contain the spillage using bunding. |
| 6.3. Methods and material for | r containment and cleaning up |
| Clean-up procedures: | Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for |
| | disposal by an appropriate method. Do not use equipment in clean-up procedure which |
| | may produce sparks. |
| 6.4. Reference to other section | |
| | |
| Reference to other sections: | Refer to section 8 of SDS. |
| Section 7: Handling and stor | age |
| 7.1. Precautions for safe han | dling |
| Handling requirements: | Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. |
| | Do not handle in a confined space. Avoid the formation or spread of mists in the air. |
| | Smoking is forbidden. Use non-sparking tools. |
| | |
| 7.2. Conditions for safe stora | ge, including any incompatibilities |
| Storage conditions: | Store in cool, well ventilated area. Keep container tightly closed. Keep away from |
| | sources of ignition. Prevent the build up of electrostatic charge in the immediate area. |
| | Ensure lighting and electrical equipment are not a source of ignition. |
| 7.3. Specific end use(s) | |
| | |
| Specific end use(s): | No data available. |

Section 8: Exposure controls/personal protection

TILE RITE RAPID DRY AEROSOL 600ML

8.1. Control parameters

Hazardous ingredients:

ACETONE

| Workplace exp | oosure limits: | R | espirable dust | | |
|---------------------------------------|---------------------------|---|-------------------------------|---------------|--|
| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL | |
| UK | 1210 mg/m3 | 3620 mg/m3 | - | - | |
| PROPANE | | | | | |
| UK | 1800 mg/m3 | 7200 mg/m3 | - | - | |
| N-BUTYL ACE | ТАТЕ | | | | |
| UK | 724 mg/m3 | 966 mg/m3 | - | - | |
| .2. Exposure co | g measures: Ensure the | re is sufficient ventilation of | 0 0 | nd electrical | |
| | | are not a source of ignition. | | | |
| Respiratory | protection: Self-contain | ned breathing apparatus mu | ust be available in case of e | emergency. | |
| Hand | protection: Protective | Protective gloves. | | | |
| Eye | e protection: Safety glas | Safety glasses. Ensure eye bath is to hand. | | | |
| Skin protection: Protective clothing. | | | | | |
| tion 9: Physic | al and chemical prop | erties | | | |
| | | | | | |

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Sweet-smelling

Viscosity: Non-viscous

Boiling point/range°C: <=35

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

Flash point°C: <21

TILE RITE RAPID DRY AEROSOL 600ML

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

| IVN | RAT | LD50 | 5500 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 3000 | mg/kg |
| ORL | RAT | LD50 | 5800 | mg/kg |

N-BUTYL ACETATE

| ORL | MUS | LD50 | 6 | gm/kg |
|-----|-----|------|-------|-------|
| ORL | RAT | LD50 | 10768 | mg/kg |

Relevant effects for mixture:

| Effect | Route | Basis |
|------------|-------|-----------------------|
| Irritation | OPT | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

TILE RITE RAPID DRY AEROSOL 600ML

Page: 7

Hazardous ingredients:

ACETONE

BLUEGILL (Lepomis macrochirus)

LC50

8300 mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

TILE RITE RAPID DRY AEROSOL 600ML

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

| Other information | |
|------------------------------|--|
| Other information: | This safety data sheet is prepared in accordance with Commission Regulation (EU) No |
| | 453/2010. |
| | * indicates text in the SDS which has changed since the last revision. |
| Phrases used in s.2 and s.3: | EUH066: Repeated exposure may cause skin dryness or cracking. |
| | H220: Extremely flammable gas. |
| | H224: Extremely flammable liquid and vapour. |
| | H225: Highly flammable liquid and vapour. |
| | H226: Flammable liquid and vapour. |
| | H304: May be fatal if swallowed and enters airways. |
| | H319: Causes serious eye irritation. |
| | H336: May cause drowsiness or dizziness. |
| | H411: Toxic to aquatic life with long lasting effects. |
| | H412: Harmful to aquatic life with long lasting effects. |
| | R10: Flammable. |
| | R11: Highly flammable. |
| | R12: Extremely flammable. |
| | R36: Irritating to eyes. |
| | R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic |
| | environment. |
| | R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the |
| | aquatic environment. |
| | R65: Harmful: may cause lung damage if swallowed. |
| | R66: Repeated exposure may cause skin dryness or cracking. |
| | R67: Vapours may cause drowsiness and dizziness. |
| Legend to abbreviations: | PNEC = predicted no effect level |
| | DNEL = derived no effect level |
| | LD50 = median lethal dose |
| | LC50 = median lethal concentration |
| | EC50 = median effective concentration |
| | IC50 = median inhibitory concentration |
| | dw = dry weight |

TILE RITE RAPID DRY AEROSOL 600ML

Page: 9

bw = body weight cc = closed cup oc = open cup MUS = mouse GPG = guinea pig RBT = rabbit HAM = hamster HMN = human MAM = mammal PGN = pigeon IVN = intravenous SCU = subcutaneous SKN = skin DRM = dermal OCC = ocular/corneal PCP = phycico-chemical properties Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.